+90 539 101 38 03 · 24/7 Breakdown Line
info@jutekglobal.com
www.jutekglobal.com

CAT POWER RANGE · 50 Hz · DIESEL GENERATOR SET

Cat 3516E Series 2,725 – 3,500 kVA



Image is representative.

2,725 – 3,500 kVA
Power range (standby)

2,180 – 2,800 kW
0.8 power factor

Cat 3516E
Engine

20,707 kg
Dry weight (max.)

Megawatt-class power for data centres, power plants, ports and large industrial sites, available for medium-voltage applications.

Quotes: +90 539 101 38 03 · info@jutekglobal.com

Generator set

Power (standby)	**2,725 – 3,500 kVA / 2,180 – 2,800 kW**
Prime power	**3,175 / 2,950 / 2,725 kVA**
Frequency / speed	**50 Hz / 1500 rpm**
Voltage	**380 – 11,000 V**
Phase / power factor	**3-phase / 0.8 pf**
Control panel	**Cat ECS 100**
Alternator	**IP23 alternator**
Emissions	**U.S. EPA Tier 2 / low NOx**

Engine

Engine	**Cat® 3516E**
Configuration	**V-16, 4-stroke, water-cooled diesel**
Bore x stroke	**170 x 215 mm**
Displacement	**78.1 L**
Compression ratio	**14.0:1**
Aspiration	**Turbo, air-to-air aftercooled**
Fuel system	**Electronic unit injector (EUI)**
Governor	**Electronic – ADEM™ A5**

Dimensions and weight (max.)

Length	**7,785 mm**
Width	**2,612 mm**
Height	**3,342 mm**
Dry weight	**20,380 – 20,707 kg**

Standard equipment

- Cat EMCP 4 / ECS control panel
- Modbus RTU customer data link
- Package-mounted radiator
- Air cleaner with service indicator
- Flanged exhaust outlet
- Fuel filters with water separator
- Busbar power connection
- IP23 alternator
- Emergency stop button
- 24 V DC system
- Caterpillar yellow paint

Optional equipment and JUTEK solutions

- EMCP 4.4 / load sharing module
- PMG (permanent magnet) excitation
- Alternator anti-condensation heater
- Engine jacket water heater
- Spring-type vibration isolators
- Heavy-duty starting system
- Battery charger
- Exhaust silencer
- Remote monitoring software
- Synchronising panel (JUTEK)

Technical data is based on Caterpillar publications, is for information only, may vary with configuration and is confirmed at quotation. kW values at 0.8 power factor. Images are representative. Cat® and Caterpillar® are registered trademarks of Caterpillar Inc.