+90 539 101 38 03 · 24/7 Breakdown Line
info@jutekglobal.com
www.jutekglobal.com

CAT POWER RANGE · 50 Hz · DIESEL GENERATOR SET

Cat C13 Series 350 – 450 kVA



Image is representative.

350 – 450 kVA
Power range (standby)

280 – 360 kW
0.8 power factor

Cat C13
Engine

50 Hz / 1500 rpm
Frequency / speed

High-output standby power for hotels, hospitals, shopping centres, factories and large construction sites; suitable for synchronised systems.

Quotes: +90 539 101 38 03 · info@jutekglobal.com

Generator set

Power (standby)	**350 – 450 kVA / 280 – 360 kW**
Frequency / speed	**50 Hz / 1500 rpm**
Voltage	**380 – 415 V**
Phase / power factor	**3-phase / 0.8 pf**
Control panel	**GCCP 1.3**
Alternator	**A-Frame alternator (IP21)**
Emissions	**Low fuel consumption / R96 – EU St…**

Engine

Engine	**Cat® C13**
Configuration	**In-line 6-cylinder, 4-stroke, water-coo…**
Bore x stroke	**130 x 157 mm**
Displacement	**12.5 L**
Compression ratio	**16.3:1**
Aspiration	**Turbo, air-to-air aftercooled**
Fuel system	**Mechanical electronic unit injector (M…**
Governor	**Electronic – ADEM™ A4**

Dimensions and weight (max.)

Length	**4,743 mm**
Width	**2,014 mm**
Height	**2,133 mm**

Standard equipment

- GCCP control panel
- Single-wall 8-hour fuel tank
- Radiator with guarded cooling fan
- Caterpillar extended life coolant
- Stainless steel flexible exhaust fitting
- IEC 3-pole circuit breaker
- Power centre (IP22)
- Integrated voltage regulator (IVR)
- Cat electronic / mechanical governor
- Fuel filters with water separator
- Vibration isolators
- Caterpillar yellow paint

Optional equipment and JUTEK solutions

- Cat GC sound-attenuated enclosure
- Industrial / critical grade silencer
- 4-pole circuit breaker
- Battery charger
- Alternator anti-condensation heater
- PMG (permanent magnet) excitation
- Emergency stop button
- Double-wall fuel tank
- Fuel tank with spill containment
- CE / EAC / GCC certification
- ATS transfer panel (JUTEK)
- Synchronising panel (JUTEK)

Technical data is based on Caterpillar publications, is for information only, may vary with configuration and is confirmed at quotation. kW values at 0.8 power factor. Images are representative. Cat® and Caterpillar® are registered trademarks of Caterpillar Inc.