+90 539 101 38 03 · 24/7 Breakdown Line
info@jutekglobal.com
www.jutekglobal.com

CAT GC SERIES · 50 Hz · DIESEL GENERATOR SET

Cat DE660 GC 660 kVA



Image is representative.

660 kVA
Standby power

528 kW
0.8 power factor

Cat C15
Engine

3,794 kg
Dry weight (max.)

High-output standby power for hotels, hospitals, shopping centres, factories and large construction sites; suitable for synchronised systems.

Quotes: +90 539 101 38 03 · info@jutekglobal.com

Generator set

Power (standby)	**660 kVA / 528 kW**
Prime power	**600 kVA / 480 kW**
Frequency / speed	**50 Hz / 1500 rpm**
Voltage	**380 – 415 V**
Phase / power factor	**3-phase / 0.8 pf**
Control panel	**GCCP 1.1**
Alternator	**A-Frame standard alternator**
Emissions	**Low fuel consumption (low BSFC)**
Ambient temperature	**Up to 55 °C**

Engine

Engine	**Cat® C15**
Configuration	**In-line 6-cylinder, 4-stroke diesel**
Bore x stroke	**137 x 171 mm**
Displacement	**15.2 L**
Compression ratio	**16.1:1**
Aspiration	**Turbo, air-to-air aftercooled**
Fuel system	**Electronic unit injector (EUI)**
Governor	**Electronic – ADEM™ A4**

Dimensions and weight (max.)

Length	**3,328 mm**
Width	**1,540 mm**
Height	**2,187 mm**
Dry weight	**3,794 kg**

Standard equipment

- GCCP 1.1 generator control panel
- Cat electronic governor (ADEM™ A4)
- A-Frame standard alternator
- Single-wall 8-hour fuel tank
- Skid-mounted radiator with guarded fan
- 3-pole circuit breaker
- 24 V battery, rack and cables
- Dry-type air cleaner
- Fuel filters with water separator
- Vibration isolators
- Caterpillar yellow paint
- Cat® Product Link™ remote monitoring

Optional equipment and JUTEK solutions

- Cat GC sound-attenuated enclosure
- Industrial / critical grade silencer
- 4-pole circuit breaker
- Battery charger
- Alternator anti-condensation heater
- PMG (permanent magnet) excitation
- Emergency stop button
- Double-wall fuel tank
- Fuel tank with spill containment
- CE / EAC / GCC certification
- ATS transfer panel (JUTEK)
- Synchronising panel (JUTEK)

Technical data is based on Caterpillar publications, is for information only, may vary with configuration and is confirmed at quotation. kW values at 0.8 power factor. Images are representative. Cat® and Caterpillar® are registered trademarks of Caterpillar Inc.