+90 539 101 38 03 · 24/7 Breakdown Line
info@jutekglobal.com
www.jutekglobal.com

CAT E SERIES · 50 Hz · DIESEL GENERATOR SET

Cat DE715E0 715 kVA



Image is representative.

715 kVA
Standby power

572 kW
0.8 power factor

Cat C18
Engine

50 Hz / 1500 rpm
Frequency / speed

High-output standby power for hotels, hospitals, shopping centres, factories and large construction sites; suitable for synchronised systems.

Quotes: +90 539 101 38 03 · info@jutekglobal.com

Generator set

Power (standby)	**715 kVA / 572 kW**
Prime power	**650 kVA / 520 kW**
Frequency / speed	**50 Hz / 1500 rpm**
Voltage	**200 – 400 V**
Phase / power factor	**3-phase / 0.8 pf**
Control panel	**GCCP 1.2**
Alternator	**A-Frame alternator, class H insulati…**
Emissions	**Low fuel consumption (low BSFC)**
Ambient temperature	**Up to 55 °C**

Engine

Engine	**Cat® C18**
Configuration	**In-line 6-cylinder, 4-stroke diesel**
Bore x stroke	**145 x 183 mm**
Displacement	**18.1 L**
Compression ratio	**14.5:1**
Aspiration	**Turbo, air-to-air aftercooled**
Fuel system	**Electronic unit injector (EUI)**
Governor	**Electronic – ADEM™ A4**

Standard equipment

- GCCP control panel
- 12-lead alternator, IP23 protection
- Voltage regulator
- IEC 3-pole circuit breaker
- Radiator with guarded cooling fan
- Caterpillar extended life coolant
- Air cleaner
- Industrial silencer
- Open-set base fuel tank / skid
- Vibration isolators
- 12 V battery, rack and cables
- Caterpillar yellow paint

Optional equipment and JUTEK solutions

- Earth fault / leakage protection
- Sound-attenuated enclosure
- Double-wall fuel tank
- Battery charger
- Alternator anti-condensation heater
- CE / EAC / GCC certification
- ATS transfer panel (JUTEK)
- Synchronising panel (JUTEK)

Technical data is based on Caterpillar publications, is for information only, may vary with configuration and is confirmed at quotation. kW values at 0.8 power factor. Images are representative. Cat® and Caterpillar® are registered trademarks of Caterpillar Inc.